

AI-202

2 x 2 USB Audio Interface



FEATURES :

- Features two inputs (Mic/Line & Instrument Level) and two outputs.
- Extreme low-Latency digital streaming.
- Switchable Phantom power.
- Supports Windows/Android & Mac iOS.
- Compatible with popular DAW softwares.
- USB 2.0 Bus-powered.
- Compact durable Aluminum body.

SPECIFICATIONS :

Type	Combo XLR Female X2/ 2 x 6.3mm TRS, Balanced
Input Impedance (Balanced)	2.2kOhm/ 18kOhm
THD+N (1kHz @ +0dBu Output)	<0.5%
S/N Ratio (1kHz @ +0dBu Output)	>55dB
Input Level (0dBu Gain, 1kHz)	3mV ±1mV / 45mV ± 2mV
Phantom Power	+48 VDC at both XLR Female only
Input Impedance	1MOhm
Frequency Response	20-20,000Hz
Pad ON	-18dB
Maximum Output ±20mV	550mV
Bit Depth	16 bit
Internal Sample Frequency Selections	44.1, 48 kHz
Power	USB Bus Powered
Dimensions	W175 × H58 × D123 mm
Weight	615g

Specifications from the official Ahuja catalogue. Issued for customer reference.