

AI-22

2 x 2 USB Audio Interface

DESCRIPTION :

The Ahuja AI-22 is a 2 x 2 USB audio interface. It has a balanced mic/line input.

Features 2 inputs (Mic/Line and Instrument Level) and 2 outputs.



FEATURES :

- Studio Quality(16Bit/48kHz) Digital Recording.
- Features 2 inputs (Mic/Line & Instrument Level) and 2 outputs.
- Extreme low-Latency digital streaming.
- Switchable Phantom power.
- Supports Windows/Android & Mac iOS.
- Compatible with popular DAW software.
- USB 2.0 Bus-powered.
- Compact durable Aluminum body.

SPECIFICATIONS :

Type	Combo XLR Female / 6.3mm (¼") TRS balanced
Frequency Response (±1.0dB)	30Hz to 20kHz
Input Impedance (Balanced)	2.2kOhm / 18kOhm
THD+N (1kHz @ +0dBu Output)	£ 0.5%
S/N Ratio (1kHz @ +0dBu Output)	>55dB
Input Level (0dBu Gain, 1kHz)	3mV (±1mV) / 35mV (±2mV)
Phantom Power (±2 VDC)	+48 VDC (at XLR female only)
Input Impedance	1MOhm
Frequency Response (±1dB)	20Hz to 20kHz
Maximum Output (±20mV)	775mV
Bit Depth	16 bit
Internal Sample Frequency Selections	44.1, 48 (kHz)
Power	USB bus-powered

Dimensions	W175 × H58 × D123 mm
------------	----------------------

Weight	550g approx.
--------	--------------

Specifications from the official Ahuja catalogue. Issued for customer reference.