

AiR 2 mixer



FEATURES :

- 2 Mic / Line + 2 Stereo Line Inputs
- 3 Band EQ per channel
- Rotary control knobs per channel
- Delay EFX on board & FX send per channel.
- Dual 10 Segment L/R LED meter for master level.
- Stereo RCA CD In & Out with Control.
- L/R Pan Pot & Clip LED per Channel
- Headphone output with control
- Balanced ¼" Jack Master outputs.

SPECIFICATIONS :

Series	AiR Series
Gain (Mic/Line)	60dB/40dB
Mic (Gain Min/Gain Max)	-5dBu / -60dBu
Line (Gain Min /Gain Max)	+6dBu / -40dBu
Main Output level (Nominal / Max)	+0dBu (0.775V RMS) / +20dBu (7.75V RMS)
Frequency Response	20Hz to 20KHz (+0/-3 dB)
Total Harmonic Distortion	< 0.03%
Signal to Noise Ratio	-85dB
Clip indication	4 dB prior to true clip
Equalisation (Treble/Mid/Bass)	±15dB @ 12KHz/2.5KHz/80 Hz
EFX	Delay with repeat
Power Supply	AC 240 V / 50Hz
Dimensions (W x D x H in mm)	190 x 245 x 85
Net Weight (Kgs.)	1.85

Specifications from the official SM Professional literature. Issued for customer reference.