

AiR 8

Mixer



FEATURES :

- 8 Mic / Line
- 3 Band EQ per channel
- 1 Aux send.
- PFL (Cue) Switch with individual channel control
- L/R pan pot and clip LED per channel.
- Stereo RCA CD input with Control.
- Delay EFX on board & FX send per channel.
- 8 Segments L/R LED meter for master level.
- Headphone output with level control
- Balanced XLR & ¼" Jack Master Output.

SPECIFICATIONS :

Series	AiR Series
Gain (Mic/Line)	60dB/40dB
Mic (Gain Min/Gain Max)	-5dBu / -60dBu
Line (Gain Min /Gain Max)	+6dBu / -40dBu
Main Output level (Nominal / Max)	+0dBu (0.775V RMS) / +20dBu (7.75V RMS)
Frequency Response	20Hz to 20KHz (+0/-3 dB)
Total Harmonic Distortion	< 0.03%
Signal to Noise Ratio	-85dB
Clip indication	4 dB prior to true clip
Equalisation (Treble/Mid/Bass)	±15dB @ 12KHz/2.5KHz/80Hz
EFX	Delay with repeat
Power Supply	AC 240 V / 50Hz
Dimensions (W x D x H in mm)	305 x 335 x 115
Net Weight (Kgs.)	3.8

Specifications from the official SM Professional literature. Issued for customer reference.