

AMA-240DP

AC & 24V DC Operation



FEATURES :

- 3 Unbalanced Mic inputs, 2 balanced Mic inputs, 2 Aux inputs, 1 Telephone & 1 balanced line Input.
- Voice Operated Priority in Mic-1 and Telephone Inputs.
- Preamplifier Output (unbal.) and Line Output (bal.) for recording & connecting a booster amplifier.

SPECIFICATIONS :

Power Output	415W Max., 325W RMS at 10% THD, 240W RMS at 1% THD
Output Regulation	2 dB, no load to full load at 1kHz
Input Channels	3 × Mic 2.5mV/4.7kOhm (unbal.), 2 × Mic 2.0mV/2kOhm (bal.), 1 × Line 1V/50kOhm
Frequency Response	50-15,000Hz ±3dB
Signal to Noise Ratio	60dB
Tone Controls	Bass: ±10dB at 100Hz, Treble: ±10dB at 10kHz
Output	Preamp 200mV/600Ohm (Unbal.), Line 1V/1kOhm (Bal.), Monitor 5V/8Ohm
Speaker Output	4Ohm, 8Ohm, 70V & 100V
Digital Player	MP3 Player with USB, SD / MMC Card Reader & Bluetooth
Power Supply	AC: 220-240V 50/60Hz DC: 24V (2×12V Car Battery)
Power Consumption	AC: 600VA DC: 7A
Dimensions	W485 × H142 × D405 mm
Weight	21.00kg

Specifications from the official Ahuja catalogue. Issued for customer reference.