

## APZ-501RM

### Remote Paging Mic Console

#### DESCRIPTION :

A high performance remote zonal paging console that works with paging controller APZ-502CU for remote paging and control over a multi-zone system.



#### FEATURES :

- A high performance remote zonal paging console that works with paging controller APZ-502CU for remote paging and control over a multi-zone system.
- Several modes (all zones, 10 zones or individual zones) can be achieved through this paging console.
- Capability to page upto 300 zones from one APZ-501RM.
- Capability of cascading (series connection with RJ 45) up to 16 microphones for paging from multiple locations.
- Operation number input keys with LED display.
- Can manage upto 30 paging controllers APZ-502CU (for 300 zones).
- Fitted with a condenser microphone with flexible 12.5 inch (31cm) gooseneck.
- Built in chime circuit.
- Recessed chime and microphone level controls.
- Elegant extruded aluminium body

#### SPECIFICATIONS :

|                               |                                                                                 |
|-------------------------------|---------------------------------------------------------------------------------|
| Input                         | MIC 600Ohm, 10mV unbalanced; Line 10kOhm, 775mV unbalanced                      |
| Output                        | Balanced                                                                        |
| Frequency Response            | MIC 100Hz-15kHz; Line 30Hz-18kHz                                                |
| S/N Ratio                     | MIC 60dB; Line 80dB                                                             |
| Controls                      | Chime and MIC volume, 300 channel selection, chime button, MIC on/off, 10 zones |
| Power Supply                  | DC 24V                                                                          |
| Communication Protocol        | RS422                                                                           |
| Communication Input and Speed | RJ45, 4800 bps                                                                  |
| Dimensions                    | W220 × H51.5 × D142.7 mm                                                        |
| Weight                        | 1.25 kg                                                                         |

Specifications from the official Ahuja catalogue. Issued for customer reference.