

CCS-2200

COUNTER COMMUNICATION SYSTEM

DESCRIPTION :

The Ahuja CCS-2200 is a counter communication system. Duplex communication technology, ideal for ticket counters, enquiry counters, banks, embassies, hospitals etc. Wherever two way communication is required across a glass barrier.

(Can also be used for one way communication). Exclusively designed lightweight plastic external unit, which can be easily mounted on any flat surface. Double sided fixing pad provided.



FEATURES :

- Unique design, pleasing aesthetics & rugged construction.
- Duplex communication technology, ideal for ticket counters, enquiry counters, banks, embassies, hospitals etc. . Wherever two way communication is required across a glass barrier. (Can also be used for one way communication).
- Compact & elegant Attendant Unit with gooseneck microphone, in black colour finish, for flexible sound pickup angle.
- Separate switches for switching the Host Unit mic, or the External Unit mic, ON or OFF.
- Separate volume controls on the Host Unit for adjusting the audio output level of the Host Unit and the External Unit.
- Host Unit mic has automatic voice priority over the External Unit mic. When attendant is speaking into the Host Unit mic, the mic of the External unit is automatically muted.
- Exclusively designed lightweight plastic external unit, which can be easily mounted on any flat surface. Double sided fixing pad provided.
- External unit houses a condenser mic cartridge and an efficient speaker for clear and intelligible sound outside the glass barrier.
- Audio output for recording available through 3.5mm phone jack on the Host Unit. This is a stereo output having signals from both the Host Unit mic and the External Unit mic.
- A 3.5mm phone jack is provided on the rear panel of the Host Unit for Line Input. This feature can be used to play back pre-recorded messages through the external unit speaker by connecting the Pre-amp output or Line Output of any Ahuja amplifier to the Line Input of the Host Unit.
- The system is easy to install and simple to operate.
- The Host Unit is a table top unit which operates on 12V DC, through an AC adapter supplied alongwith.

SPECIFICATIONS :

Output	2 × 5W (Max.) in each amplifier
Microphone Element	Electret Condenser in both the units.
Frequency Response	100Hz-10KHz
Power Requirement	AC: 220-240V, 50/60Hz
Speaker impedance	4Ohm each
Dimensions	Host Unit : W179.7 x H129.8 x D56.5mm, External Unit : W117.8 x H83.7 x D38.9mm
Weight	Host Unit : 590g approx., External Unit : 190g approx.
Accessories	1 PC Host Unit, 1 PC External Unit, 1 PC AC adapter, 1 PC User Manual, 1 PC AC Adapter

Specifications from the official Ahuja catalogue. Issued for customer reference.

