

DC 12.2UX

DESCRIPTION :

The DC 12.2UX is part of the SM Professional Diamond Club Series - one of the best-selling and the most trusted mixing consoles in India.

The 12 channel mixer features high-quality delay EFX onboard, USB/SD card MP3 media player with transport control and IR remote control, and built-in Bluetooth connectivity for wireless streaming.



FEATURES :

- 12 mic / line + USB / SD card input for MP3 music playback with IR remote control.
- Built-in Bluetooth wireless streaming from smartphones, tablets and laptops.
- High-quality on-board delay EFX with time and repeat control.
- 2 Aux sends / returns.
- 1 pre & post aux sends rotary control per channel.
- Balanced mic / line input.
- Gain control with 3 band EQ per channel.
- L/R pan pot, illuminated mute switch & clip LED per channel.
- Stereo tape in / tape out and 1/4" headphone out.
- Balanced 1/4" TRS L/R master output.
- 12 segments L/R LED meter for master level output.

SPECIFICATIONS :

Series	Diamond Club Series
Nominal Gain (Mic/Line)	60dB/40dB
Max Gain (Mic/Line)	76dB/56dB
Mic (Gain Min/Gain Max)	-12dBu / -60dBu
Line (Gain Min /Gain Max)	+8dBu / -40dBu
Mic Input	Typically 5K Ohm balanced
Line input	20K Ohm (Balanced) /10K Ohm (Unbalanced)
Main Output level (Nominal / Max)	0dBu (0.775V RMS) / +17dBu (5.5V RMS)
Main Output Impedance	<50 Ohm
Frequency Response	25Hz to 19KHz (+0/-1 dB)
Total Harmonic Distortion	Better than 0.8%
Signal to Noise Ratio	-76 dB
Clip indication	4 dB prior to true clip

Equalisation (Treble/Mid/Bass)	±16dB @ 10KHz/2.5KHz/100 Hz
EFX & USB	USB+SD+MMC+EFX
Power Supply	150V~250V AC/50Hz
Dimensions (W x D x H in mm)	555x376x89
Net Weight (Kgs.)	8.5

Specifications from the official SM Professional literature. Issued for customer reference.