

DJA 4000

Power Amplifier



FEATURES :

- Input: Balanced XLR & 1/4" Jack.
- EQ Processing, Low Cut, Subwoofer selection options on rear panel.
- Stereo, Bridge & Parallel mode selection switch.
- Protection: Temperature ,DC Short Circuit.
- Large cooling Fans.
- LED Indicators on front panel for power, Signal, Clip, bass boost & Protect.
- Mains voltage operation 220V AC-240V AC as well as low voltage operation (150V AC).
- Output: Speakon & Binding Post Connectors.
- 19" rack mountable.

SPECIFICATIONS :

Series	DJA Series
4 Ohm (True RMS),20Hz-20kHz,1% THD	2 x 1400 W
4 Ohm (EIA), 1kHz , 1%THD	2 x 1950 W
8 Ohm (True RMS),20Hz-20kHz,1% THD	2 x 900 W
8 Ohm (EIA), 1kHz , 1%THD	2 x 1100 W
8 Ohm (True RMS), 20Hz-20kHz, 1% THD	2800 W
8 Ohm (EIA), 1kHz , 1%THD_	3900 W
Damping factor	> 350 :1 (8 Ohm)
Frequency Response	20Hz - 20kHz (-3dB)
Protection Devices	Temperature, DC, Short Circuit, Soft Start
Input Connector (Per Channel)	XLR, 1/4" TRS Jack
Output Connector (Per Channel)	Speakon / Binding Posts
Dimensions (W x D x H)mm	482 x 495 x 132 (3U)
Net Weight (Kgs.)	29.5

Specifications from the official SM Professional literature. Issued for customer reference.