

F18.120

Loudspeaker



FEATURES :

- Professional-grade 18" (460mm) diameter extended low-frequency transducer.
- Features a high-endurance 4" (100mm) diameter inside/outside Copper voice coil.
- Designed to deliver 1200W (RMS) to 2400W (Peak) power output.
- Ventilated voice coil gap for reduced power compression.
- Deep frequency range of 33Hz to 3.5kHz.
- Impressive sensitivity of 98 dB (1w @1m).
- Integrates a high-quality Ferrite magnet for maximum sonic performance.
- Heavy-duty die-cast frame with a wide flange for increased rigidity.
- Engineered to reproduce high power bass and sub-bass frequencies efficiently.
- Optimized to suit a wide variety of enclosure designs.

SPECIFICATIONS :

Series	Fury Series
Product Type	Subwoofer
Power Output (RMS / Peak) Watts	1200 / 2400
Frequency Response	33Hz-3.5kHz
Impedance (Ohm)	8
Sensitivity (1w @ 1m) dB	98
Nominal Diameter (mm/inch)	460/18
Voice Coil Diameter (mm/Inch)	100 / 4
Voice Coil Material	Copper
Kind of Layer	Inside / Outside
Basket	Die-cast
Net Weight (Kg)	10.3

Specifications from the official SM Professional literature. Issued for customer reference.