

SD 300

DESCRIPTION :

The SM Professional SD 300 is a compact high-quality digital delay EFX processor ideal for a variety of singing, musical, and vocal applications in live, touring, and public address scenarios.



FEATURES :

- High-performance digital delay EFX processor.
- Features 2 x professional-grade 1/4" unbalanced Mic/Line inputs and 1 x output.
- Inputs switchable between Mic and Line.
- Delay time and repeat control for a variety of effect options.
- Individual level controls for the inputs and effect output.
- Convenient effect ON/OFF or bypass switch.
- Works on +12V DC adapter as well as +9V DC battery.
- Elegant look with a compact build size for easy portability.

SPECIFICATIONS :

Input Impedance (Mic / Line)	> 2.5 K / > 20 K
Sensitivity Mic / Line	- 34dB (15.5mV) / - 3.5dB (518mV)
S/N Ratio Mic / Line	>65 / >70
THD	0.10%
Frequency Response Mic / Line	0 dB @ 50Hz - 15kHz / 0 dB @ 50Hz - 20kHz
Current Consumption	55 mA DC Max.
Dimensions (W x D x H)	90 x 93 x 55 mm.
Net Weight (GMS)	400

Specifications from the official SM Professional literature. Issued for customer reference.