SRX-50DX

PA Speaker System

DESCRIPTION :

The Ahuja SRX-50DX is a 50W PA speaker system with 2×8" LF woofer.

A compact general purpose Loudspeaker column using two Full Range Dual Cone 20.32 cm (8") speakers, reproducing a clean undistorted sound for both speech and music.

FEATURES :

- A compact general purpose Loudspeaker column using two Full Range Dual Cone 20.32 cm (8") speakers, reproducing a clean undistorted sound for both speech and music.
- The system is housed in a Rugged Closed Box Enclosure made of 12 mm medium density fibre board, and is carpet covered.
- SRX-50DX has nominal impedance of 16Ohm, SRX-50XT operates on 100V line with three power taps selectable through a rotary switch.

SPECIFICATIONS :

Input Power	50W Max.
Power Taps	30/20/10W at 100V
Configuration	One Way
Frequency Response	55-16,000Hz
Low Frequency Speaker	2 x 203.2 mm (8"), Ø19.05 mm (0.75") Voice Coil
SPL at (1W/1m)	96dB
Max. Rated SPL	113dB
Nominal Impedance	16Ohm / 333/500/1kOhm
Port	Sealed Enclosure
Input Connectors	Two nos. of Terminal Strip in parallel
Dimensions	W325 × H585 × D240 mm / W325 × H605 × D240 mm
Weight	9.20kg / 9.60kg

Specifications from the official Ahuja catalogue. Issued for customer reference.