

VaK 10

Installation Product



FEATURES :

- Highly flexible & customizable system supporting 4 Chairman & 160 Delegate Units.
- 4 Channels - Each channel supports 40 delegate units Total 160 units), & up to 4 chairman units.
- NOM (Number of Open Microphones) - Supports up to 8 active delegate units.
- NOM based gain adjustment.
- Fully automatic no operator required.
- User friendly interface with LCD display.
- Attractive look & finish.
- Balanced XLR & 1/4" Jack Master output.
- AUX & Line output for recording or monitoring.
- Output signal level controls.
- 19", 2U Rack Unit Design.
- Intelligent algorithm & DSP audio processing system.
- Detachable & Flexible gooseneck microphone.
- High Quality Panasonic® microphone capsule ensures good voice reproduction.
- LED Indicator on Microphone, to indicate 'Mic Active' status.
- Built-in speaker with level control.
- 2 Separate Headphone output.
- Priority Switch to override all delegate units. (Only on VaK 10.c)

SPECIFICATIONS :

Series	VK Series
Frequency Response	100-14.5kHz
S/N	81dB
Audio Output	RCA x 2, 1/4" Jack x 1, XLR x 1
Audio Input/Output (TEL)	RCA x 2
Power Supply	AC 230V/50Hz
Dimension (WxDxH) mm	483 x 323 x 90
Frequency Response_	100Hz-10kHz
S/N_	70dB

Connection	Round 8P-DIN x 2 M
Sensitivity	-50dB/Pa
Length of MIC Tube	400mm
Length of Cable	2.1m
Power Supply_	DC24V
Dimension (WxDxH) mm_	160 x 175 x 65 / Mic: 533mm (L)

Specifications from the official SM Professional literature. Issued for customer reference.