

Vok 40

fully wireless conferencing system

DESCRIPTION :

The SM Professional Vok 40 is a fully wireless conferencing system with camera tracking, digital voting, and much more.

Integrating state-of-the-art Digital Signal Processing technologies, premium-grade hardware, unmatched interoperability, and an easy user interface, the Vok 40 series is geared to deliver a powerful, and intuitive wireless conferencing experience.



FEATURES :

- Professional wireless conference system with 4 operating modes, FIFO / LIFO / Limit / Chairman.
- Highly-flexible and customizable system supporting up to 200 units.
- 10 secure UHF channels with editable frequencies for flexibility in complex applications.
- NOM (Number of Open Microphones) - Supports up to 4 active units.
- Remote microphone ON/OFF and shutdown.
- Built-in USB MP3 recorder with sequential file saving and storage.
- Intuitive camera tracking with industry-standard VISCA and PELCO D/P protocol compatibility.
- RS-232 and RS-485 camera controller interface.
- Easy sign-in and voting function for streamlined decision making.
- Automatic interference correction and anti-RF for dropout-free performance.
- DSP and noise gate for ambient noise suppression and audio clarity.
- Operating distance of up to 100 ft. (line of sight).
- User-friendly interface with responsive LCD touch screen.
- Easy-to-use, no operator required.
- Quick plug-and-play installation.
- Ideal for boardrooms, conference rooms, legislative chambers and other large and complex meeting scenarios.
- Sleek and classy 21" 2-bend gooseneck microphone with base.
- High-quality condenser microphone capsule for superior voice reproduction.
- Illuminated ON/OFF talk switch.
- Clear 2" TFT colour screen displays microphone ON/OFF status, connectivity status, selected channel number, unit ID, battery level, microphone ON time and analogue watch dial.

FEATURES :

- LED ring to indicate 'Mic Active' status.
- Priority switch on the chairman unit to override all delegates during a discussion.
- Quick access switches to sign-in for voting function, increase/decrease volume and microphone number editing.
- Power supply options: Removable rechargeable battery or USB type-C connector (cable supplied).
- Long-lasting 20 hours battery life.
- Fully wireless for flexibility in fixed and mobile applications.

SPECIFICATIONS :

Series	VK Series
Frequency Range (Hz)	45Hz-18kHz $\pm$ 1dB
Signal to Noise Ratio	>60dB
Operation Distance	60m
Output Connector	XLR & 1/4" Jack
Power Supply	3.7V DC
Dimension (W x D X H) mm	483 x 323 x 90
Net Weight (Kg)	0.76
RF Power Output	15mW
Priority Button	Only on the Vak 40.c Chairman Unit
Bandwidth	30MHz
Length of MIC Tube	21" / 533mm (2 Bends)
Dimension (W x D x H) mm	160 x 138 x 49

Specifications from the official SM Professional literature. Issued for customer reference.