

Vak 50

Installation Product



FEATURES :

- 10 balanced Inputs & Outputs.
- Professional digital wired conference system.
- Seamless network connectivity via standard RJ45 ethernet connectors.
- Supports up to 100 participants by default for small to medium meeting scenarios.
- Can support up to 1000 participants via optional extender for larger meeting scenarios.
- Multifunctional operating modes such as FIFO, LIFO, chairman, all ON, auto mode and more.
- Advanced priority control with manual and auto recover options.
- Remote microphone ON/OFF and shutdown.
- Built-in USB MP2 recorder with sequential file saving and storage.
- RS-232 and RS-485 camera controller interface.
- Supports one camera system out-of-the-box and multi camera systems via optional extender.
- Embedded browser-based web management app for remote configuration and control via a PC, laptop or smartphone.
- User-friendly interface with responsive LCD touch screen.
- Quick plug-and-play installation, easy-to-use, no operator required.
- Ideal for boardrooms, conference rooms, legislative chambers and other large and complex meeting scenarios.
- 12 V Lamp Socket.

SPECIFICATIONS :

Operating Distance	Between 2 microphones (2m)
Balanced Output Level	-4dBV
Frequency Response	100Hz-10KHz
Signal to Noise Ratio	80dB
Connector for chairman/delegate	RJ45
Audio Input Connector	Line: RCA X 1, TEL: RCA X 1
Audio Output Connector	Line: XLR x 1, RCA x1, TEL: RCA x 1
Line Sensitivity	-15dB

Power Supply	AC 220 V, 50Hz
Dimension (W x D X H) mm	483 x 326 x 90
Net Weight (Kg)	0.75
Microphone Sensitivity	-50dB/Pa
Microphone Polar Pattern	Cardioid
Connection with Main Controller	RJ45
Length of Cable	1.5m
Length of MIC Tube	215mm (Shortneck) / 540mm (Gooseneck) 2 Bends
Priority Button	Only on the Vak 50.c Chairman Unit
Max. Current Consumption	60mA
Dimension (W x D x H)mm	148 x 124 x 60 (Base)

Specifications from the official SM Professional literature. Issued for customer reference.