

Zone 66

DESCRIPTION :

The SM Professional Zone 66 is a 6 zone paging system designed for a variety of environs such as Factories, Hospitals, Schools, etc.



FEATURES :

- 6 Mic/Line inputs switchable to 6 outputs with independent Gain control, 2 band equalizer, Level control & CLIP led.
- One Stereo channel with 4-way input selector Gain control, 2 band equalizer, Level control & CLIP led.
- Matrix assignment : Each input channel can be assigned to any combination of output(s).
- Each Microphone input is with low noise preamplifier & +48V Phantom voltage selection switch.
- 6 mono outputs with level controls & 6-digit LED level meter.
- Input connectors: 6X Line (Stereo RCA) , 6X Mic (XLR) & 4X Aux (Stereo RCA).
- Output connectors: 6X (XLR balanced and RCA Unbalanced).

SPECIFICATIONS :

Input Gain (Mic / Line)	+12 to +60dB
Output Level	+6dB
Frequency Response	20Hz - 20KHz
Signal to Noise RatioMic / Line	Better than -75dB / Better than -85dB
THD (Mic / Line)	< 1% / <0.05%
Tone Control - Bass / Treble	± 12dB / 100Hz / ±12dB / 10kHz
Input Connectors	6 x Line (Stereo RCA), 6 x Mix (XLR) & 4 x Aux (Stereo RCA)
Output Connectors	6 x (XLR balanced and RCA Unbalanced)
Dimensions (W x D x H)mm	483 x 172.5 x 133 (3 U)
Net Weight (Kgs.)	4.8

Specifications from the official SM Professional literature. Issued for customer reference.